

BR2A DTH HAMMER

BR2A. Hammers	Item Description	Weight (Kg)	Part Number
	1 Top Sub	2.95	BR2A-TSUB
	2 Check Valve	0.10	BR2A-CVALVE
	3 Spring	0.05	BR2A-SPRING
	4 Air Distributor	0.40	BR2A-DIST
	5 Internal Cylinder	0.85	BR2A-ICYL
	6 Piston	2.70	BR2A-PISTON
	7 External Cylinder	5.35	BR2A-ECYL
	8 Guided Sleeve	0.55	BR2A-BUSH
	9 "O" Ring Stop Ring	0.005	BR2A-SR-SRING
	10 Stop Ring	0.10	BR2A-SRING
	11 Drive Chuck	1.05	BR2A-DCHUCK
	12 Drill Bit		BR2A-76FF-TV

Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
880mm	14.1kg	Φ62mm	BR2	Φ76-Φ90	RD 50 BOX
Box Size	Impact rate at 1.7Mpa	Recommended rotation speed	Air Consumption		
			80-170(PSI)		
910x90x120mm	25HZ	25-40r/min	250-350(CFM)		