

HD45 DTH HAMMER

HD45. Hammers	Item Description	Weight (Kg)	Part Number	
	1	Top Sub	6.50	HD45-TSUB
	2	"O"Ring of Top Sub	0.01	HD45-SR-TSUB
	3	Check Valve	0.42	HD45-CVALVE
	4	Spring	0.04	HD45-SPRING
	5	Compression Buffer	0.04	HD45-CBUFFER
	6	Air Distributor	2.20	HD45-DIST
	7	Internal Cylinder	2.30	HD45-ICYL
	8	Piston	9.00	HD45-PISTON
	9	External Cylinder	15.8	HD45-ECYL
	10	"O" Ring of Stop Ring	0.01	HD45-SR-SRING
	11	Stop Ring	0.20	HD45-SRING
	12	Drive Chuck	3.50	HD45-DCHUCK
	13	Drill Bit		HD45-115FF-TV

Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
1030mm	40.0Kg	Φ99	Cop44 DHD340 HD45	Φ112-Φ127	API 3 1/2 " REG
Box Size	Impact rate at 1.7Mpa	Recommended rotation speed	Air Consumption		
			200-300(PSI)		
1150x130x160mm	27HZ	25-40r/min	500-700(CFM)		