

# HK4-D DTH HAMMER

HK4-D. Hammers	Item Description	Weight (Kg)	Part Number
	1 Top Sub	6.50	HK4-D-TSUB
	2 "O"Ring of Top Sub	0.01	HK4-D-SR-TSUB
	3 Check Valve	0.35	HK4-D-CVALVE
	4 Spring	0.05	HK4-D-SPRING
	5 Compression Buffer	0.15	HK4-D-CBUFFER
	6 Air Distributor	2.10	HK4-D-DIST
	7 Internal Cylinder	2.25	HK4-D-ICYL
	8 Piston	8.50	HK4-D-PISTON
	9 External Cylinder	15.2	HK4-D-ECYL
	10 Guided Sleeve	1.30	HK4-D-BUSH
	11 "O"Ring of Stop Ring	0.01	HK4-D-SR-SRING
	12 Stop Ring	0.30	HK4-D-SRING
	13 Drive Chuck	3.40	HK4-D-DCHUCK
	14 Drill Bit		HK4-D-110FF-TV

## Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
922mm	38.0Kg	Φ100	DHD340A Cop44	Φ112-Φ127	API 2 3/8 " REG
Box Size	Impact rate at 1.7Mpa	Recommended rotation speed	Air Consumption		
			200-300(PSI)		
1010x130x160mm	25HZ	30-70r/min	500-700(CFM)		