

HK8-Q DTH HAMMER

HK8-Q. Hammers	Item Description	Weight (Kg)	Part Number
	1 Top Sub	34.0	HK8-Q--TSUB
	2 "O"Ring of Top Sub	0.02	HK8-Q-SR-TSUB
	3 Check Valve	0.95	HK8-Q-CVALVE
	4 Spring	0.10	HK8-Q-SPRING
	5 Compression Buffer	0.35	HK8-Q-CBUFFER
	6 Air Distributor	6.05	HK8-Q-DIST
	7 Internal Cylinder	6.25	HK8-Q-ICYL
	8 Piston	38.0	HK8-Q-PISTON
	9 External Cylinder	56.0	HK8-Q-ECYL
	10 Guided Sleeve	5.30	HK8-Q-BUSH
	11 Retaining Ring	0.20	HK8-Q-RRING
	12 Stop Ring	1.90	HK8-Q-SRING
	13 Drive Chuck	13.0	HK8-Q-DCHUCK
	14 Drill Bit		HK8-Q-203CC-TV

Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
1340mm	172.0Kg	Φ185	QL80	Φ203-Φ229	BECO 4 1/2" REG API 4 1/2" REG
Box Size	Impact rate at 1.7Mpa	Recommended rotation speed	AirConsumption		
			300-380(PSI)		
1440x230x270mm	25HZ	30-70r/min	950-1200(CFM)		